


Standard length tolerance	
L (inches)	Tolerance (inches)
2.0 - 5.9	+/-0.125
6.0 - 11.9	+/-0.187
12.0 - 23.9	+/-0.250
24.0 - 35.9	+/-0.313
36.0 - 47.9	+/-0.375
48.0 - 59.9	+/-0.500
60.0 - 71.9	+/-0.563
72.0 - 83.9	+/-0.625
>83.9	Please contact evissap

Description:

- Frequency range: DC – 67 GHz
- VSWR ≤ 1.40:1 through 67 GHz
- Raw cable insertion loss is 1.97dB / FT @ 67 GHz
- Phase stability vs flexure @ 6" diameter coil : +/- 8 deg @ 67 GHz
- Amplitude Stability vs Flexure @ 6" diameter coil: <0.1 dB @ 67 GHz

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED	SIZE A	SCALE NO	
	REV. A	SHEET 1/1	
CAGE CODE: 4KGK3	Title: eP7099R		Title: 1.85mm M to 1.85mm M Armored low loss phase stable

Contact us:
E-mail: sales@evissap.com

Sample test data for eP7099R-0.9M (0.9-meter length cable)

