


Description:

- Frequency range: DC – 26.5 GHz
- VSWR ≤ 1.35:1 @ 26.5 GHz, 100% VSWR tested prior to shipment
- Raw cable insertion loss is ~0.62 dB / FT @ 40 GHz

| Standard length tolerance | |
|---------------------------|------------------------|
| L (inches) | Tolerance (inches) |
| 2.0 - 5.9 | +/-0.125 |
| 6.0 - 11.9 | +/-0.187 |
| 12.0 - 23.9 | +/-0.250 |
| 24.0 - 35.9 | +/-0.313 |
| 36.0 - 47.9 | +/-0.375 |
| 48.0 - 59.9 | +/-0.500 |
| 60.0 - 71.9 | +/-0.563 |
| 72.0 - 83.9 | +/-0.625 |
| >83.9 | Please contact evissaP |

| | | | |
|---|-------------------|--------------|---|
| All DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED | SIZE A | SCALE NO |  |
| | REV. A | SHEET 1/1 | |
| CAGE CODE: 4KGK3 | Title: eP7125R | | Title: 3.5mm Male to 3.5mm Male Ultra Low Loss Cable |

Contact us:
E-mail: sales@evissap.com

Sample test data for eP7125R-9.0 (9 inch length)

