



The RG58 Flexible cable with black PVC jacket offers users high quality, low cost flexible jumper cable. The stranded center conductor and PVC jacket give user excellent flexibility to bend the cable inside equipment. evissap offers its RG58 Flexible cable assemblies in a wide variety of connector configurations, RG58 Flexible cable assemblies are built using lead free solder in combination with state-of-the-art induction soldering techniques.

Features

- RG58 Flexible
- N Male and N Male connectors
- 100% VSWR test to 3 GHz
- 100% Hi-pot and continuity tests
- Standard delivery <21 days from order
- RoHS compliant per evissap RoHS statement

Overview

Impedance	50 ohms
Frequency Range	DC-3 GHz
Cable	RG58
Cable O.D.	.195" nominal

Configuration

Connector 1	N Male
	Ni-plated brass body
	Ni plated coupling nut
Connector 2	N Male
	Ni-plated brass body
	Ni plated coupling nut

Application

- WLL, GPS, WLAN
- Mobil Antennas
- Wireless Communication Sysytem

evissap Standards

When ordering, please specify cable assembly length in inches. Example: eP2072R-12.5 specifies a 12.5" long cable assembly
Label will have evissap P/N and Date Code
Shipment will include evissap's standard C of C.
evissap web posted warranty and Ters and Conditions applies
FOB is evissap's San Jose, CA US facility

Connector options available for .085" cable

- * BNC ST and RT/A male, female and bulkhead
- * Type N ST and RT male, female and bulkhead
- * TNC ST and RT male, female and bulkhead

Electrical Specifications @ +25°C		Unit
Frequency range	DC-3	GHz
Maximum VSWR	1.35	:1
Cable Typical velocity of propagation	69.5	%


Typical Performance @+25°C	DC-1 GHz	1-2 GHz	2-3 GHz
VSWR (S11) (:1) typ. max.@ 12 in.	1.08	1.18	1.14
Insertion Loss (S21) (dB) typ. max. @12 in.	0.25	0.4	0.55

For any length (L in.), estimated insertion loss: $C + (S21 \text{ value above-C}) * (L/12)$, Connector loss is $C = 2 * .03 \sqrt{f(\text{GHz})}$


Bulk cable specifications	
Temperature range	-25 to +75° C
Cable Type	RG58
Cable outer diameter	.195" nominal
Inner conductor/finish	Copper Tin plated
Dielectric type	PE
Jacket material	PVC

Connector specifications	Connector 1	Connector 2
Configuration	Straight	Straight
Connector Type	N male	N male
Body hex size	N/A	N/A
Coupling nut hex size	N/A	N/A
Coupling nut material/finish	Ni plated brass	Ni plated brass
Connector body material/finish	Ni plated brass	Ni plated brass
Dielectric type	PTFE	PTFE

Typical performance data for 12" cable @+25°



Outline drawing



Standard length tolerance	
L (inches)	Tolerance (inches)
2.0 - 5.9	+/-0.125
6.0 - 11.9	+/-0.187
12.0 - 23.9	+/-0.250
24.0 - 35.9	+/-0.313
36.0 - 47.9	+/-0.375
48.0 - 59.9	+/-0.500
60.0 - 71.9	+/-0.563
72.0 - 83.9	+/-0.625
>83.9	Please contact evissaP

evissaP offers its RG58 Flexible cable assemblies in a wide variety of connector configurations, RG58 Flexible cable assemblies are built using lead free solder in combination with state-of-the art induction soldering techniques. If you cannot find the exact eP-formable cable assembly you require, please submit a request along with your requirement information.

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by evissaP, Inc. ("eP") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of evissaP. evissaP reserves the right to change specifications, prices and any other information at any time without prior notice.